

# ATV SEAT COVER



## CLEANING

You can hand wash your seat cover in warm water or machine wash in COLD water. DO NOT USE SOAP as it can damage the protective coatings on the fabric. Line dry or machine dry on air or delicate.

## STORAGE

Be sure that your seat cover is completely dry before you store it for an extended period in a confined space.

## WARRANTY

Your seat cover is factory warranted for workmanship and materials for one year after purchase.

## INSTALLATION

1. Remove the seat from your ATV. This is usually easy—look for a latch near the back of the seat. If you're not sure how to unlatch your seat consult your ATV owner's manual.
2. Check for any sharp edges that could stress your seat cover. Now stretch your seat cover over the seat with the label in the seat cover hem at the front of your seat. Be sure that your seat cover is not covering the latching mechanism.
3. Reattach your ATV seat to your ATV.



WE COVER YOUR GEAR™

Classic Accessories, Inc.  
Kent, WA, USA 98032  
[www.classicaccessories.com](http://www.classicaccessories.com)

©2007

78387, 78386 07cA53\_6874

# COUVRE-SIÈGE DE VTT



## NETTOYAGE

Nettoyez le couvre-siège avec de l'eau tiède ou lavez-le en machine à l'eau FROIDE. NE PAS UTILISER DE SAVON car il risque d'endommager le revêtement protecteur de la toile. Accrochez-le sur une ligne de séchage ou placez-le dans le sèche-linge en réglant la machine sur « air » ou sur un cycle de séchage pour articles délicats.

## REMISAGE

Pour éviter toute apparition de moisissure, assurez-vous que le couvre-siège est complètement sec avant de le remettre pour une longue période dans un espace clos.

## GARANTIE

Le couvre-siège est garanti par l'usine contre tout vice de matériau et de fabrication pendant une durée d'un an à partir de la date d'achat.

## INSTALLATION

1. Enlevez le siège de votre VTT. C'est en général assez facile, il suffit de localiser le loquet à l'arrière du siège. Si vous n'êtes pas sûr, consultez le manuel d'utilisation de votre VTT.
2. Assurez-vous qu'il n'y a pas de bords coupants qui risqueraient de tirer sur le couvre-siège. Ensuite, étirez le couvre-siège par-dessus le siège, en plaçant l'étiquette du couvre-siège à l'avant du siège. Assurez-vous que le couvre-siège ne recouvre pas le mécanisme de verrouillage du siège.
3. Refixez le siège sur le VTT.



WE COVER YOUR GEAR™

NOUS PROTÉGEONS VOTRE ÉQUIPEMENT

Classic Accessories, Inc.  
Kent, WA, USA 98032  
[www.classicaccessories.com](http://www.classicaccessories.com)

©2007

78387, 78386 07cA53\_6874