

# Instructions: Four Layer Deluxe Car Cover

## Caution

- Never cover a wet vehicle
- Not liable for repainted surfaces or lacquer paint
- Do not cover the tail pipe or exhaust
- A hot exhaust and muffler can burn you and melt your cover
- Be sure the hood and engine are cool before you put on your cover
- Never cover a convertible with the top down
- Do not spread cover across an open sunroof or T-roof

This cover is designed to be water resistant and repellent but it will not prevent water from reaching the surface of your vehicle.

## Installation

Remove or retract your antenna. If you have a fixed antenna see below. Pull your cover over the roof from the back to the front. Drop your cover over the sides, then fit the elastic hem of your cover under the front bumper of your vehicle. Secure your cover under the rear bumper and corners.

## Antennas

Check your antenna—many antennas simply unscrew at their base. If your antenna cannot be removed or retracted, you will need to make a small hole in your cover for it.

Put your cover on as much of your vehicle as you can without

covering the antenna. Mark the area where your cover will go over the antenna. With a sharp pencil or pen, carefully push a small hole in your cover. Peel the backing from your antenna patch and, centering the hole in the patch over the hole in your cover, adhere the patch to your cover. Press the patch down firmly. Carefully lift your cover down over your antenna, threading your antenna through the hole, and finish fitting your cover.

## Cable & lock set

Your car cover comes with a cable and lock set you can secure through the grommets located on either side of the bottom hem of your car cover. See instructions and diagram with the cable and lock.

## Care

Clean your cover with a soft brush and lukewarm water or machine wash in COLD water. DO NOT USE SOAP as it may remove the protective coating added by the factory. Line dry only; do not machine dry. Avoid trapping moisture under your cover. If your vehicle is outside for long periods or under snow, trapped moisture can sometimes cause paint to become cloudy. We recommend removing your cover every 30 days. Let your vehicle dry completely before reinstalling your cover.



## Storage

A handy storage bag is provided for your cover. Be sure the cover is completely dry before you store it in the storage bag for an extended period.

## Four Year Warranty

This product is factory warranted for workmanship and materials for four years after purchase. Trailering or use during transportation of your vehicle will invalidate this warranty.



WE COVER YOUR GEAR™

Classic Accessories, Inc.  
Kent, WA, USA 98032  
[www.classicaccessories.com](http://www.classicaccessories.com)

©2007