

Instructions: Deluxe PolyPro III™ Jeep Cover

Caution

- Never cover a wet vehicle
- Not liable for repainted surfaces or lacquer paint
- Do not cover the tail pipe or exhaust
- A hot exhaust and muffler can burn you and melt your cover
- Be sure the hood and engine are cool before you put on your cover
- Never cover a convertible with the top down
- Do not spread cover across an open sunroof or T-roof

This cover is designed to be water resistant and repellent, but it will not prevent water from reaching the surface of your vehicle.

Installation

Remove or retract your antenna. See below if you have a fixed antenna.

Look for the tag sewn in the hem that says Front. This is the front of your cover. Pull your cover over the roof from the front to the back. Drop your cover over the sides, then fit the elastic hem of your cover under the front bumper of your vehicle. Secure your cover under the rear bumper and corners.

Antennas

Check your antenna—many antennas simply unscrew at their base. If your antenna cannot be removed or retracted, you will need to



make a small hole in your cover for it.

Put your cover on as much of your vehicle as you can without covering the antenna. Mark the area where your cover will go over the antenna. With a sharp pencil or pen, carefully push a small hole in your cover. Peel the backing from your antenna patch and, centering the hole in the patch over the hole in your cover, adhere the patch to your cover. Press the patch down firmly. Carefully lift your cover down over your antenna, threading your antenna through the hole, and finish fitting your cover.

Care

Clean your cover with a soft brush and lukewarm water. DO NOT USE SOAP as it may remove the protective coating added by the factory. Line dry only; do not machine dry.

Avoid trapping moisture under your cover. If your vehicle is outside for long periods or under snow, trapped moisture can sometimes cause paint to

become cloudy. We recommend removing your cover every 30 days. Let your vehicle dry completely before reinstalling your cover.

Storage

A handy storage bag is provided for your cover. Be sure the cover is completely dry before you store it in the storage bag for an extended period.

Three Year Warranty

This product is factory warranted for workmanship and materials for three years after purchase. Trailering or use during transportation of your vehicle will invalidate this warranty.



Classic Accessories, Inc.
Kent, WA, USA 98032
www.classicaccessories.com
©2007